

Date: 05/04/2016

# R-FLUSH

#### ADVANCED COOLING SYSTEM CLEANER

#### **DESCRIPTION**

High-Tech blend of inorganic acids and inhibitors, designed for effective removal of: rust, lime scale build up, oily residues and deposits from engines cooling systems.

#### **BASIC BENEFITS**

- Restores the normal circulation of coolant in the system and eliminates risk of overheating.
- Restores the optimal operation of the controls within the cooling system.
- · Safe for rubber hoses, seals and all metals in the cooling system.

#### **PROPERTIES**

- Effectively removes rust, lime scale deposits and oily residues.
- · Protects the cooling system from contaminations and clogging.
- · Protects cooling systems against corrosion and oxidation.
- · Excellent performance in all types of cooling liquid, including OAT coolant.

#### **APPLICATION**

Recommended for water cooled systems of all petrol and diesel engines.

## **DIRECTIONS FOR USE**

- · Run the engine until it reaches it operating temperature and thermostat has opened fully.
- · Put the heater control to HOT position, open and drain the cooling system.
- When empty, close system and add R-Flush to radiator or cooling system, refill with water.
- · Start the engine, run at idle for approximately 20 minutes.
- Stop the engine and allow to cool, open drain valve and empty the system.
- · While the system remains open, flush with water until clear water comes out.
- · Close system and refill with coolant.
- 300 ml is suitable for 4 to 10L of coolant.

### **TYPICALS**

Physical state: liquid
Colour: farblos
pH-Value (at 20°C): 9,5
Melting point: < 0 °C
Initial boiling point

and boiling range: > 100 °C Flash point: > 100 °C Ignition temperature: 410 °C

Auto-ignition temperature:

Solid: Undetermined. Gas: Undetermined.

Decomposition temperature:

Oxidizing properties:

Vapour pressure:

Density (at 20 °C):

Water solubility (at 20 °C):

Partition coefficient:

Undetermined.

not oxidizing.

Undetermined.

1,05 g/cm³

1000 g/L

Undetermined.

Flow time: > 30 s

Evaporation rate: Undetermined.

## **PACKAGING**

300 ml can (12 x 300 ml carton) - 1L can (12 x 1L carton)

